

# Master

## 9.4 or 10.4 metres

For arable and grassland

### Standard equipment:

- Self-cleaning Prisma roller® Ø45/50 cm **cast iron**
- Six pendular elements with **3D ground contouring**
- Drawbar with hitch Cat. 3
- Transport wheels 15.0/55-17 10 PR
- Hydraulic pivoting
- Road lighting kit (LED)



### Standard machine

Type	Working width	Transport width	Num. of sections	Support load	Axle load	Weight	Item Num.	Price excl. VAT
Master 940 with brake	9.30 m	3.00 m	6	1,670 kg	2,970 kg	4,845 kg*	5101 5000-3	
Master 940 with brake	9.30 m	3.00 m	6	1,675 kg	2,970 kg	4,995 kg	5101 5033	
Master 1040 with brake	10.40 m	3.00 m	6	1,850 kg	3,180 kg	5,290 kg	5101 6033	

\* For total weights more than 3.000 kg consider the traffic regulations!

### Optional extras

Descriptor	Note	Weight	Item Num.	Price excl. VAT
Wheels 19.0/45-17 14 PR	Surcharge on wheels 15.0/55-17 10 PR	120 kg	5102 1180	
NonStop-harrow for Master 940	3-rows, 12 mm tines, space between tines 62.5 mm <b>Air brakes necessary</b>	2,100 kg	5001 2000-1	
NonStop-harrow for Master 940	2-rows, with levelling bar, space between tines 75 mm <b>Air brakes necessary!</b>	2,100 kg	5001 2500-1	
NonStop-harrow for Master 940	2-rows, with Ripperboard, space between tines 37.5 mm <b>Air brakes necessary!</b> <b>Hydraulic pitch adjustment Ripperboard</b>	2,200 kg 200 kg	5001 2510-1 5001 2520	
NonStop-harrow for Master 1040	3-rows, 12 mm tines, space between tines 62.5 mm	2,200 kg	5001 2100-1	
NonStop-harrow for Master 1040	2-rows, with levelling bar, space between tines 75 mm	2,200 kg	5001 2600-1	
NonStop-harrow for Master 1040	2-rows, with Ripperboard, space between tines 37.5 mm <b>Hydraulic pitch adjustment Ripperboard</b>	2,300 kg 200 kg	5001 2610-1 5001 2620	
Hydraulic pressure compensation	incl. throttle screw, manometres, gas accumulator for a constant pressure distribution at the cantilevers		5102 1500	
Loose tines	DPT unit with loose tines and quick-connect latch	300 kg	5019 8978	

### Additional information

Additional information	Note
NonStop-harrow	Standard with straight tines (Item Num. with -1). Optional with cranked tines (Item Num. without -1), same price.
Final assembly roller on-site:	approx. 3 hours
Final assemb. NonStop-harrow on site:	approx. 2 hours
Hydraulic connections required:	2x da (Master - pivoting and transport wheels) 1x da (for hydraulic pitch adjustment Ripperboard)

### Working elements



NonStop-harrow 3-rows  
Item Num. 5001 2000 for Master 940  
Item Num. 5001 2100 for Master 1040



NonStop-harrow 2-rows  
with levelling bar  
Item Num. 5001 2500 for Master 940  
Item Num. 5001 2600 for Master 1040



NonStop-harrow 2-rows  
with Ripperboard  
Item Num. 5001 2510 for Master 940  
Item Num. 5001 2610 for Master 1040  
Option: Hydraulic pitch adjustment for  
Ripperboard