

OffSet®

4.8 or 6.4 metres

For arable and grassland

Standard equipment:

- Self-cleaning Prisma roller® Ø45/50 cm **cast iron**
- Drawbar with hitch Cat. 2
- Transport wheels 11.5/80-15 10 PR
- Hydraulic pivoting
- Road lighting kit (LED)



Standard machine

Type	Working width	Transport width	Num. of sections	Support load	Axle load	Weight	Item Num.	Price excl. VAT
OffSet® 480	4.80 m	2.40 m	5	500 kg	2,055 kg	2,555 kg	5200 6664	
with FlatSpring 480				495 kg	2,455 kg	2,950 kg		see options
OffSet® 640	6.30 m	2.40 m	5	440 kg	2,500 kg	2,940 kg	5200 5661-1	
with FlatSpring 640				460 kg	2,860 kg	3,320 kg*		see options

*For total weights more than 3.000 kg consider the traffic regulations!

Optional extras

Descriptor	Note	Weight	Item Num.	Price excl. VAT
FlatSpring 480	Hydraulic connections required: 1x da	395 kg	5200 4480	
FlatSpring 640	Hydraulic connections required: 1x da	380 kg	5200 4630	
Drawbar extension	Only necessary for coupling to the GreenMaster or mounting of a seeder!	50 kg	5200 4100	

Additional information

Descriptor	Note
OffSet® Final assembly on-site:	Approx. 1 hour! Attention: Minimum 2m long forks will be necessary to unload the roller from the lorry!
Required Hydraulic connections:	1x da (OffSet®) 1x da (FlatSpring)



Consider the traffic regulations! See page 5.