

Super Maxx[®] BIO

5.0 | 6.0 metres hydraulic folding
5-rows



5-rows

Standard equipment: BIO

- Front gauge wheels 18.5 x 8.5-8
- Harrow with tines Ø12 mm
- Road lighting kit (LED)
- Gap between tines for rear gauge wheels

Standard machine

| Type BIO | Working width | Transport width | No. of tines | Note | Weight | Item no. | Price excl. VAT |
|----------------------------------|---------------|-----------------|--------------|---|----------|-------------|-----------------|
| Super Maxx [®] 50-5 BIO | 4.80 m | 2.50 m | 37 | hydr. folding, 4 gauge wheels, headstock cat. 2/3 | 1,560 kg | 4503 1500-2 | |
| Super Maxx [®] 60-5 BIO | 5.80 m | 2.50 m | 45 | hydr. folding, 4 gauge wheels, headstock cat. 2/3 | 1,770 kg | 4503 1600-2 | |

Options

| Description | Note | Weight | Item no. | Price excl. VAT |
|-----------------|---|--------|-------------|-----------------|
| 2nd harrow row | incl. console for Super Maxx [®] 50 | 215 kg | 4502 1550-2 | |
| 2nd harrow row | incl. console for Super Maxx [®] 60 | 245 kg | 4502 1650-2 | |
| Crumbler roller | mounting instead of a harrow for Super Maxx [®] 50 | 135 kg | 4502 3050 | |
| Crumbler roller | mounting instead of a harrow for Super Maxx [®] 60 | 162 kg | 4502 3060 | |

Retrofit kit on levelling bar 1st row + harrow 2nd row

Instead of the harrow supplied as standard, a levelling bar is used in the 1st row. The harrow supplied as standard is installed in the 2nd row with the also supplied consoles.

| | | | | |
|--|---|--------|-------------|--|
| Retrofit kit levell. bar | levelling bar + consoles 2nd row for Super Maxx [®] 50 | 180 kg | 4502 1571K | |
| Retrofit kit levell. bar | levelling bar + consoles 2nd row for Super Maxx [®] 60 | 200 kg | 4502 1671K | |
| 2 Rear swiveling gauge wheels | swiveling gauge wheel 18,5 x 8,5-8 -2 pcs. for gap between tines | 90 kg | 4502 9070-1 | |
| 2 Rear swiveling gauge wheels reinforced | swiveling gauge wheel 195/55 R10 - 2 pcs. for gap between tines | 110 kg | 4502 9079-1 | |
| Front gauge wheels reinforced | surcharge for heavy duty gauge wheels 195/55 R10 - 4 pcs., mounted ex factory | 100 kg | 4502 9075 | |
| Tarpaulin for tines | tarpaulin for Super Maxx [®] 50 + 60 5-rows | 20 kg | 4500 1650 | |

Options are added separately and have to be assembled on-site!

Hydraulic adjustment **NEW**

| Description | Note | Weight | Item no. | Price excl. VAT |
|-----------------------------------|---|--------|-----------|-----------------|
| 1st Hydraulic harrow row | surcharge for hydraulic tilt adjustment for Super Maxx [®] 50 60 | 50 kg | 4500 5815 | |
| 2nd Hydraulic harrow row | surcharge for hydraulic tilt adjustment for Super Maxx [®] 50 60 | 53 kg | 4500 5825 | |
| Retrofit kit 1st hydraulic harrow | Hydraulic tilt adjustment for 2. hydraulic row Super Maxx [®] 50 60 70, for self-assembly | 50 kg | 4500 5810 | |
| Retrofit kit 2nd hydraulic harrow | Hydraulic tilt adjustment for 2. hydraulic row Super Maxx [®] 50 60 70, for self-assembly | 53 kg | 4500 5820 | |

Additional Information

| Additional Information | Note |
|---|---|
| Final assembly Super Maxx [®] on-site: | approx. 1/2 hour Super Maxx [®] 50 and 60 |
| Required hydraulic connections: | 1x da (Super Maxx [®] 50 + 60 - folding) 1x da for hydraulic harrow adjustment (optional) |
| Final assembly hydraulic harrow: | 1st harrow row approx. 2 hours, 2nd harrow row approx. 1 hour |

