

# Master

## 6.4 or 7.7 or 8.2 metres

For arable and grassland

### Standard equipment:

- Self-cleaning Prisma roller® Ø45/50 cm **cast iron**
- Four pendular elements with **3D ground contouring**
- Drawbar with hitch Cat. 2
- Transport wheels 15.0/55-17 10 PR
- Hydraulic folding
- Road lighting kit (LED)



### Standard machine

Type	Working width	Transport width	Num. of sections	Support load	Axle load	Weight	Item Num.	Price excl. VAT
Master 640	6.30 m	3.00 m	4	1,180 kg	2,170 kg	3,350 kg*	5100 9020-4	
Master 770	7.60 m	3.00 m	4	1,260 kg	2,440 kg	3,700 kg*	5100 9040-4	
Master 820	8.10 m	3.00 m	4	1,320 kg	2,580 kg	3,900 kg*	5100 9045-4	

\* For total weights more than 3.000 kg consider the traffic regulations!

### Optional extras

Descriptor	Note	Weight	Item Num.	Price excl. VAT
Wheels 19.0/45-17 14 PR	Surcharge on wheels 15,0/55-17 10 PR	120 kg	5102 1180	
FlatSpring for Master 640*	Hydraulic connections required: 4x da Final assembly on-site: approx. 2 hours <b>Air brakes necessary!</b> <b>Recommended wheels: 19,0/45-17 14 PR</b>	890 kg	5100 9640*	
FlatSpring for Master 770*	Hydraulic connections required: 4x da Final assembly on-site: approx. 2 hours <b>Air brakes necessary!</b> <b>Recommended wheels: 19,0/45-17 14 PR</b>	1,060 kg	5100 9660*	
Air brakes 640	Dual-circuit system. Necessary for axle loads more than 3.000 kg!	150 kg	8501 6000	
Air brakes 770   820	Dual-circuit system. Necessary for axle loads more than 3.000 kg!	150 kg	8501 6100	
Connecting pipe for air brakes	Necessary if a roller with air brakes is linked with a GreenMaster		7400 1011	
Loose tines	Coupling frame with loose tines and quick-connect latch	300 kg	5019 8978	

\* With fitted FlatSpring it is not possible to link the Master roller with a GreenMaster

### Pneumatic seeder

Name	Note	Weight	Item Num.	Price excl. VAT
660 litres hydraulic fan*	Description see page 20, final assembly on-site approx. 2 hours	130 kg	8202 2041-1*	
Console Master 640 for Pneumatic seeder 660 litres*	For mounting the Pneumatic seeder with 660 litres on the Master roller, <b>mounted ex factory</b>	200 kg	8202 20025-1	
Console Master 770 for Pneumatic seeder 660 litres*	For mounting the Pneumatic seeder with 660 litres on the Master roller, <b>mounted ex factory</b>	200 kg	8202 20026-1	
Console Master 820 for Pneumatic seeder 660 litres*	For mounting the Pneumatic seeder with 660 litres on the Master roller, <b>mounted ex factory</b>	200 kg	8202 20028-1	

\* With fitted seeder it is not possible to link the Master roller with a GreenMaster

Additional information	Note
final assembly on-site:	Roller: approx. 2 hours / FlatSpring: approx. 1 hour / seeder: approx. 2 hours
Hydraulic connections required:	2x da (Master – pivoting and transport wheels) 2x da (FlatSpring – pivoting and inclination adjustment) 1x single acting and 1x pressureless return for pneumatic seeder with hydraulic fan



Master 770 with fitted seeder 660 litre

### Attention:

With fitted seeder it is not possible to link the Master roller with a GreenMaster!