

SUPER MAXX[®] 1000-7 / 1200-7 BIO

10 or 12 metres BIO. Hydraulically folding with ground wheels
7-rows

Standard equipment:

- Hydraulic folding
- FlatSpring hydraulically adjustable FlatSpring
- Fully adjustable harrow
- Transport wheels with compressed air brake system
- Road lighting kit (LED)
- Transport tarpaulin for tines
- **Expert report for obtaining the general operating licence**



7-rows

Standard machine without FlatSpring

Type	Working width	Transport width	Num. of tines	Note	Item Num.	Price excl. VAT
Super Maxx [®] 1000-7	10.00 m	3.00 m	77	Depth guidance via transport wheels with drawbar (6 additional tines)	4501 0010	
Super Maxx [®] 1200-7	12.00 m	3.00 m	93	Depth guidance via transport wheels with drawbar (6 additional tines)	4501 0020	

Basic machine with FlatSpring

Type	Working width	Transport width	Num. of tines	Support load	Axle load	Weight	Item Num.	Price excl. VAT
Super Maxx [®] 1000-7	10.00 m	3.00 m	77	2,950 kg	5,400 kg	8,350 kg*	4501 0000	
Super Maxx [®] 1200-7	12.00 m	3.00 m	93	3,150 kg	5,550 kg	8,700 kg*	4501 2000	

* Total weights over 3 tons may require an operating license to drive on public roads in your country!

Optional extras

Descriptor	Note	Weight	Item Num.	Price excl. VAT
2nd row	incl. Console for Super Maxx [®] 1000-7		9700 9775	
2nd row	incl. Console for Super Maxx [®] 1200-7		4501 2050K	
Loosening tines for Super Maxx [®] 1000-7 - 1200-7	4 tines mounted at the drawbar Quick-change system for points with swept point		5101 0051	

Additional information

Total length:	10.0 m
Transport width:	3.0 m
Transport height:	4.0 m
Hydraulic connections required:	3x da (1x transport wheels, 1x pivfolding, 1x FlatSpring)
Final assembly of the Super Maxx [®] on-site:	approx. 2 hours (delivery on low-loader with excess width)

