

# SUPER MAXX<sup>®</sup> CULTI

**3,0 metres rigid frame | 5,0 | 6,0 metres hydraulic folding**  
5-ROWS

## Standard equipment: CULTI

- Levelling bar
- RollFix Ø45 cm Synthetic Ultra
- Road lighting kit (LED)



## Standard machine

Type	Working width	Transport width	Num. of tines	Note	Weight	Item Num.	Price excl. VAT
Super Maxx <sup>®</sup> 30-5 CULTI	2.85 m	3.00 m	22	5-rows set-up rigid frame headstock Cat. 2	1,065 kg	4503 0305K	
Super Maxx <sup>®</sup> 50-5 CULTI	4.80 m	2.50 m	37	5-rows set-up hydraulic folding headstock Cat. 2/3	1,980 kg	4503 1505K	
Super Maxx <sup>®</sup> 60-5 CULTI	5.80 m	2.50 m	45	5-rows set-up hydraulic folding headstock Cat. 2/3	2,190 kg	4503 1605K	

## Optional extras

Descriptor	Note	Weight	Item Num.	Price excl. VAT
Harrow behind roller	For Super Maxx <sup>®</sup> 30-5 CULTI	70 kg	4502 0360K	
Harrow behind roller	For Super Maxx <sup>®</sup> 50-5 CULTI	130 kg	4502 1560K	
Harrow behind roller	For Super Maxx <sup>®</sup> 60-5 CULTI	140 kg	4502 1660K	
Ripperboard QUATTRO	For Super Maxx <sup>®</sup> 50-5 CULTI, hydraulically adjustable	300 kg	4502 1580K	
Ripperboard QUATTRO	For Super Maxx <sup>®</sup> 60-5 CULTI, hydraulically adjustable	350 kg	4502 1590K	
2 Front gauge wheels / use adapter with long hole	For Super Maxx <sup>®</sup> 30 CULTI, size: 18.5 x 8.5-8	45 kg	4502 9094K	
4 front gauge wheels / use adapter with long hole	For Super Maxx <sup>®</sup> 50 + 60 CULTI, size: 18.5 x 8.5-8	90 kg	4502 9098K	
Adapter with long hole for Linkage Cat.2	When using front gauge wheels		9700 9750	
Adapter with long hole for Linkage Cat.3	When using front gauge wheels		9700 9118-1	
Transport tarpaulin for tines	Tarpaulin for Super Maxx <sup>®</sup> 50 + 60		4500 1650	

**Options are added separately and have to be assembled on-site!**

## Additional information

Additional information	Note
Final assemb. of the Super Maxx <sup>®</sup> on-site:	approx. ½ hour for Super Maxx <sup>®</sup> 50 and 60 – 3 hours for Super Maxx <sup>®</sup> 30-5
Required hydraulic connections:	1x da (Super Maxx <sup>®</sup> 50 + 60 - pivoting) 1x da (Super Maxx <sup>®</sup> 50 + 60 - hydraulic inclination adjustment Ripperboard)



5-rows with levelling bar and RollFix 45



Ripperboard QUATTRO,  
pitch control hydraulically adjustable in work  
height-adjustable with adjusting spindle