

# WOX AERMASTER

## Pasture maintenance



**With many different variations in the Güttnler Greenmaster range the Aermaster has come about as one of the adaptations to it - a 3.0m version.**

The Aermaster can be used on its own, with a weight frame attached, to allow penetration into the ground. It can be attached to the front of the Greenmaster 300 and thus the inherent weight of the Greenmaster keeps the Aermaster in the ground.

Floating arms on the Aermaster give the machine the opportunity to move in stoney conditions, supported by the "C Flex" hangers that carry the shafts.

The Aermaster can also be filed in lieu of the Harrowflex if the overall weight is an issue with the tractor availability and possible poor ground conditions. This then allows the Harrowflex from the Greenmaster to be front mounted.

### Technical detail:

- Standard 3.0m machine with 7 left handed and 7 right handed fully "timed" and "twisted" Genesis Tines
- 'C' Flex hangers give stone protection and vibration protection while the ground is hard and dry
- Adjustable for pitch gang angling in 2.5 degree increments
- 3 point hitch for attachment to the Güttnler Greenmaster 300
- 3 point hitch allows to be rear mounted on its own with a weight frame

Type	Working width	Transport width	Weight	Item Num.	Price excl. VAT
Aermaster 300	3.0m	3.0m	860kg		

