

SIMPLEX 56

4.1 to 7.2 metres with hydraulic folding

(For sandy soil, from light to heavy soils)

Standard equipment:

- Front press with Güttnler® Simplex roller in **special cast iron ø56 cm**
- Headstock Cat. 2 for front linkage
- U-stand



Standard machine

| Type | Working width | Transport width | Note | Weight | Item Num. | Price excl. VAT |
|-----------|---------------|-----------------|------------------------------|----------|-------------|-----------------|
| SX 420-56 | 4.10 m | 3.00 m | 3.00 m + 2x 0.60 m U-folding | 1,790 kg | 6155 3420-1 | |
| SX 460-56 | 4.54 m | 3.00 m | 3.00 m + 2x 0.80 m U-folding | 1,875 kg | 6155 3460-1 | |
| SX 510-56 | 5.07 m | 2.70 m | 1.80 m + 2x 1.60 m U-folding | 1,960 kg | 6155 0510-1 | |
| SX 610-56 | 6.15 m | 2.70 m | 1.80 m + 2x 2.10 m U-folding | 2,100 kg | 6155 0610-1 | |
| SX 720-56 | 7.20 m | 3.00 m | 3.00 m + 2x 2.10 m U-folding | 2,300 kg | 6155 3720 | |

Tined unit, space between tines of 150 mm, 3 rows, c/w side plates

| Type | Working width | Transport width | Note | Weight | Item Num. | Price excl. VAT |
|---------------|---------------|-----------------|--|--------|-----------|-----------------|
| For SX 420-56 | 4.00 m | 3.00 m | 3.00 m + 2x 0.50 m, rear headstock not poss.! | 550 kg | 6154 3420 | |
| For SX 460-56 | 4.50 m | 3.00 m | 3.00 m + 2x 0.75 m, rear headstock not poss.! | 600 kg | 6154 3460 | |
| For SX 510-56 | 5.00 m | 2.70 m | 2x 2.50 m | 580 kg | 6154 1510 | |
| For SX 610-56 | 6.00 m | 2.70 m | 2x 3.00 m | 640 kg | 6154 1610 | |

FlatSpring hydraulically adjustable Attention: 1 additional da control unit necessary!

| Type | Working width | Transport width | Note | Weight | Item Num. | Price excl. VAT |
|---------------|---------------|-----------------|--|--------|-----------|-----------------|
| For SX 420-56 | 4.00 m | 3.00 m | 2x 2.00 m, hydraulic inclination adjustment | 250 kg | 6153 3420 | |
| For SX 460-56 | 4.50 m | 3.00 m | 2x 2.25 m, hydraulic inclination adjustment | 280 kg | 6153 3460 | |
| For SX 510-56 | 5.00 m | 2.70 m | 2x 2.50 m, hydraulic inclination adjustment | 310 kg | 6153 1510 | |
| For SX 610-56 | 6.00 m | 2.70 m | 2x 3.00 m, hydraulic inclination adjustment | 365 kg | 6153 1610 | |
| For SX 720-56 | 7.00 m | 3.00 m | 3.00 m + 2x 2.00 m, rear headstock not poss.! | 400 kg | 6153 3720 | |

Road lighting kit (LED)

| Type | Note | Weight | Item Num. | Price excl. VAT |
|-----------------------------|--|--------|-----------|-----------------|
| For Simplex 420-56 - 720-56 | for front linkage, mounted ex factory | 20 kg | 1127 3400 | |
| For Simplex 420-56 - 720-56 | for front linkage with tined unit / FlatSpring (3-parted), mounted ex factory | 20 kg | 9700 7214 | |
| For Simplex 420-56 - 610-56 | for front linkage with tined unit / FlatSpring (2-parted) mounted ex factory | 20 kg | 1127 3410 | |
| For Simplex 420-56 - 720-56 | for rear linkage (w/o rear headstock), mounted ex factory | 20 kg | 1127 3420 | |
| For Simplex 420-56 - 720-56 | for rear linkage (with rear headstock), mounted ex factory | 20 kg | 1127 3430 | |

Optional extras

| Descriptor | Note | Weight | Item Num. | Price excl. VAT |
|---|---|--------|-----------|-----------------|
| Helpers for tined unit | Price per unit, mounted ex factory | | 4200 0290 | |
| Helpers for tined unit | Price per unit as retrofit kit, for self-assembly | | 4200 0280 | |
| Transport wheels with drawbar | Plug in coupling for trailed press conversion | 400 kg | 6150 1020 | |
| Rear headstock long for Simplex 420-56 - 610-56 | with tined unit or FlatSpring | 220 kg | 6150 1010 | |
| Hydraulic change over block | for hydraulic adjustment of the FlatSpring (saves 1x da control unit) | | 9700 7581 | |

Additional information

| Additional information | Note |
|--------------------------------|---------------------------------------|
| Required hydraulic connections | 1x da (Simplex) 1x da (FlatSpring) |



Consider the traffic regulations! Restricted visibility must be observed.
Equipment list for front devices see page 5.