


Data Sheet

Güttler® Greenmaster 600 Compact | **GÜTTLER®**

- 2 rows of NonStop-tines, $\varnothing 12$ mm, with a 75mm space between tines
- Protection against loss of tines
- Hydraulic folding with pressure compensation (3 sections)
- Headstock Cat. II and III
- Full road lighting kit (LED)
- Hydraulic fan as standard - PTO fan as a no cost option
- QUATTRO Ripper board as standard, fully adjustable for depth and rake
- 410l, 660l hopper with mechanical or ISO connection for metering
- Parking support stands, mounted on the machine when not deployed
- Mediana Roller 33/38cm self-cleaning cast roller - Synthetic Ultra options upon request (reduced weight)
- Working width 6.2m - Transport width 3.0m - Transport height 3.3m (with ground clearance of 0.25m)



Güttler® SeedProfi "High" Control

It is now even easier to seed precisely and accurately!

- Display terminal with a 5" colour monitor and magnetic mounting plate
- Electronically controlled seeding shaft drive with daily and total area counter
- Manual predosing / calibration
- Theoretical hopper level indication during work
- Incremental rate change in 5% steps + or -
- USB-connection for software updates
- Connection cable for driving speed detection
- Calibration and hopper drain button on the control box
- Fan speed with air flow monitoring (for prevention of blocked pipes)

