

# Avant 56 with tined unit

## 2.5 to 4.0 metres rigid frame

(for heavy tractors, fast working speeds, light sandy soils, heavy and loamy soils)

### Standard equipment:

- Front press with Güttler Simplex Roller® in special cast iron Ø56 cm
- Rear scraper fitted on the Simplex Prisma Roller®
- Headstock Cat. 2 for front linkage
- Tined unit – space between tines 15 cm, 3-rows
- Side plates for the tined unit



### Standard machine

Type	Working width	Transport width	Roller	Num. of tines	Prism rings	Weight	Item Num.	Price excl. VAT
Avant 26-56 with t.u.	2.50 m	2.60 m	SX 26-56 SG	15	19	1,050 kg	4200 4025	
Avant 30-56 with t.u.	2.92 m	3.00 m	SX 30-56 SG	17	22	1,150 kg	4200 4030	
			Levelling bar behind the tines, <b>for self-assembly</b>			130 kg	7400 4575	
Avant 35-56 with t.u.	3.26 m	3.50 m	SX 33-56 SG	21	25	1,300 kg	4200 4035	
Avant 41-56 with t.u.	4.00 m	4.10 m	SX 41-56 SG	25	30	1,500 kg	4200 4040	

### Road lighting kit (LED)

Type	Note	Weight	Item Num.	Price excl. VAT
For front linkage	Frame 80 x 50 mm, <b>for self-assembly</b>	15 kg	1127 3100-2	
For rear linkage	Frame 140 x 140 mm, <b>for self-assembly</b>	15 kg	1127 3210-2	

### Optional extras

Descriptor	Note	Weight	Item Num.	Price excl. VAT
Headstock	for rear linkage	153 kg	8030 8400	
Helpers for tined unit	Price per piece, <b>mounted ex factory</b>		4200 0290	
Helpers for tined unit	Price per piece as retrofit kit, <b>for self-assembly</b>		4200 0280	

Solo Simplex 56 Prisma Rollers® with three-point headstock can be found on page 64/65.

# Avant 56 with FlatSpring

## 3.0 metres rigid

(for heavy tractors, fast working speeds, light sandy soils, heavy and crumbly soils)

### Standard equipment:

- Front press with Güttler Simplex Roller® in special cast iron Ø56 cm
- Rear scraper fitted on the Simplex Prisma Roller®
- Headstock Cat. 2 for front linkage
- FlatSpring hydraulically adjustable



Length: 1,70 Meter

### Standard machine

Type	Workng width	Transport width	Roller	Num. of tines	Prism rings	Weight	Item Num.	Price excl. VAT
Avant 30-56 with FS	2.92 m	3.00 m	SX 30-56 SG	9	22	1,150 kg	4200 4031	

Attention: 1 additional da control unit necessary!

### Road lighting kit (LED)

Type	Note	Weight	Item Num.	Price excl. VAT
For front linkage	Frame 140 x 140 mm, <b>for self-assembly</b>	25 kg	1127 3150	
For rear linkage	Frame 140 x 140 mm, <b>for self-assembly</b>	15 kg	1127 3210-2	

### Optional extras

Descriptor	Note	Weight	Item Num.	Price excl. VAT
Headstock	for rear linkage	153 kg	8030 8400	