

**GH HILCOFLEX AGRO**

Bore size in mm/inches	Weight per metre in g	Wall thickness in mm	Working pressure in bar	Max. working pressure in bar	Burst pressure in bar	Breaking strength in kg
102 / 4"	1,350	3.5	16	20	50	12,400
114 / 4½"	1,450	3.7	15	18	45	12,400
127 / 5"	1,700	3.9	15	18	45	17,000
152 / 6"	1,950	3.9	14	17	42	17,900
180 / 7"	1,950	3.9	14	17	42	24,000

**GH HILCOFLEX AGRO EXTRA**


Bore size in mm/inches	Weight per metre in g	Wall thickness in mm	Working pressure in bar	Max. working pressure in bar	Burst pressure in bar	Breaking strength in kg
102 / 4"	1,400	3.8	16	20	50	12,400
114 / 4½"	1,450	4.0	15	18	45	12,400
127 / 5"	1,950	4.2	15	18	45	17,000
152 / 6"	2,250	4.2	14	17	42	17,900
180 / 7"	3,500	4.5	10	12	30	26,900

**Advantages**


- ✓ Unbeatable resistance to ageing and O-zone
- ✓ Outstanding abrasion resistance, even on difficult ground surfaces
- ✓ Very good resistance to fertilizers, agricultural chemicals and microorganisms
- ✓ Very high tensile strength, low pressure loss and elongation
- ✓ Excellent adhesion between the rubber and jacket lining
- ✓ Tough and durable (heavy duty)
- ✓ Transport hose for watering and drainage
- ✓ Irrigation, especially pivot systems

\*Same advantages for both Agro and Agro Extra





Scan **HERE** to learn more about drag hose



Scan **HERE** to learn more about couplings

**metal 360**