



Respect the traffic regulations!
See page 5.

GREENMASTER 600 TINE SEED

6.0 metres hydraulic folding | For pasture maintenance, overseeding and seeding of new swards (Direct seeding into the sward)

Standard equipment:

- 2-rows NonStop-tines Ø12 mm with seed tubes
- 80 tines with space between tines 75 mm
- Protection against loss of tines
- Hydraulic folding
- 4 double gauge wheels with scrapers
- Headstock Cat. 2 and Cat. 3
- Road lighting kit (LED)
- Pneumatic seeder 660 litre hopper
- Hydraulic fan



Working width: 6.0 metres
(3.00 metres + 2x 1.50 metres)

Standard machine

Type	Working width	Transport width	Transport height	Weight	Item Num.	Price excl. VAT
GreenMaster harrow 600 TINE SEED	6.00 m	3.00 m	3.10 m*	880 kg	4600 0600	

* Transport height with ground clearance of 0,25 metres

Options for harrow

Type	Working width	Note	Weight	Item Num.	Price excl. VAT
Levelling bar 600	6.00 m	For levelling, for self-assembly	250 kg	4600 1086	
Ripperboard 600 QUATTRO	6.00 m	For remediation, for self-assembly	300 kg	4600 1849	
Coupling kit STANDARD		For trailed roller, mounted ex factory	15 kg	4600 1601	
Coupling kit STANDARD, retrofit kit		For trailed roller, for self-assembly	15 kg	4600 1603	
Coupling kit PREMIUM		For trailed roller, mounted ex factory	20 kg	4600 1602	
Coupling kit PREMIUM, retrofit kit		For trailed roller, for self-assembly	20 kg	4600 1604	
Connecting pipe for air brakes of the roller		for self-assembly	10 kg	7400 1011	

Further information regarding options GreenMaster harrow, see page 29.

Pneumatic seeder

Type	Note	Weight	Item Num.	Price excl. VAT
660 litre hydraulic fan TINE SEED	Tine seed with large hydr. fan, mounted ex factory	150 kg	8202 2122-1	
Equipment 600 TINE SEED	Distribution systems and seed pipes, mounted ex factory	40 kg	4600 0640	
Console 600 for Pneumatic seeder 660 litre TINE SEED	For mounting the Pneumatic seeder 660 litre on the GreenMaster 600 TINE SEED, mounted ex factory	80 kg	4600 0620	

Options For Pneumatic seeder

Type	Note	Item Num.	Price excl. VAT
Area meter (ha)	Day- and total counter battery-powered, for self-assembly	7006 0601	
electrical seed rate setting	Seed rate adjustable from the tractor cab, for self-assembly	8202 2072	
Hydraulic lifting for ground drive wheel	For GreenMaster 600 + 750 + 800 with seeding wheel, for self-assembly , required hydraulic connection: 1x single acting	78432 9027	
Retrofit kit 600 from tine seed to broadcast seed	16 splash plates for 32 mm seed pipes with seeding bar, quick connector for 16 seed pipes, for self-assembly	4600 0170	

Further options for Pneumatic seeder see page 20.

Total GreenMaster 600 TINE SEEDER

Examples	Weight	Price excl. VAT
GreenMaster harrow 600 TINE SEEDER + Levelling bar + Pneumatic seeder 660 litre hydraulic + seeder mounting kit	1,400 kg	
GreenMaster harrow 600 TINE SEEDER + Ripperboard QUATTRO + Pneumatic seeder 660 litre hydraulic + seeder mounting kit	1,450 kg	

Additional information	Note
Assembly time for completion:	Mounting of Levelling bar or Ripperboard approx. 1.0 hour