

# SIMPLEX 56 SU

## 4.1 to 7.1 metres with hydraulic folding

(For sandy soil, from light to heavy soils)

### Standard equipment:

- Front press with Güttler® Simplex roller in **Synthetic Ultra ø56 cm**
- Headstock Cat. 2 for front linkage
- U-stand



### Standard machine

Type	Working width	Transport width	Note	Weight	Item Num.	Price excl. VAT
SX 420-56 SU	4.10 m	3.00 m	3.00 m + 2x 0.60 m U-folding	1,470 kg	6156 3420	
SX 460-56 SU	4.54 m	3.00 m	3.00 m + 2x 0.80 m U-folding	1,510 kg	6156 3460	
SX 510-56 SU	5.07 m	2.70 m	1.80 m + 2x 1.60 m U-folding	1,600 kg	6156 0510	
SX 610-56 SU	6.15 m	2.70 m	1.80 m + 2x 2.10 m U-folding	1,750 kg	6156 0610	
SX 710-56 SU	7.10 m	2.70 m	1.80 m + 2x 2.65 m U-folding	1,920 kg	6156 0710	

### Tined unit Culti, space between tines of 150 mm, 3 rows, c/w side plates

Type	Working width	Transport width	Note	Weight	Item Num.	Price excl. VAT
For SX 420-56	4.00 m	3.00 m	3.00 m + 2x 0.50 m, <b>rear headstock not poss.!</b>	550 kg	6154 3420	
For SX 460-56	4.50 m	3.00 m	3.00 m + 2x 0.75 m, <b>rear headstock not poss.!</b>	600 kg	6154 3460	
For SX 510-56	5.00 m	2.70 m	2x 2.50 m	580 kg	6154 1510	
For SX 610-56	6.00 m	2.70 m	2x 3.00 m	640 kg	6154 1610	

### FlatSpring hydraulically adjustable Attention: 1 additional da control unit necessary!

Type	Working width	Transport width	Note	Weight	Item Num.	Price excl. VAT
For SX 420-56	4.00 m	3.00 m	2x 2.00 m, hydraulic inclination adjustment	250 kg	6153 3420	
For SX 460-56	4.50 m	3.00 m	2x 2.25 m, hydraulic inclination adjustment	280 kg	6153 3460	
For SX 510-56	5.00 m	2.70 m	2x 2.50 m, hydraulic inclination adjustment	310 kg	6153 1510	
For SX 610-56	6.00 m	2.70 m	2x 3.00 m, hydraulic inclination adjustment	365 kg	6153 1610	

### Road lighting kit (LED)

Type	Note	Weight	Item Num.	Price excl. VAT
For Simplex 420-56 - 710-56	for front linkage, <b>mounted ex factory</b>	20 kg	1127 3400	
For Simplex 420-56 - 460-56	for front linkage with tined unit (3-parted), <b>mounted ex factory</b>	20 kg	9700 7214	
For Simplex 420-56 - 610-56	for front linkage with tined unit / FlatSpring (2-parted) <b>mounted ex factory</b>	20 kg	1127 3410	
For Simplex 420-56 - 710-56	for rear linkage (w/o rear headstock), <b>mounted ex factory</b>	20 kg	1127 3420	
For Simplex 420-56 - 710-56	for rear linkage (with rear headstock), <b>mounted ex factory</b>	20 kg	1127 3430	

### Optional extras

Descriptor	Note	Weight	Item Num.	Price excl. VAT
Helpers for tined unit	Price per unit, <b>mounted ex factory</b>		4200 0290	
Helpers for tined unit	Price per unit as retrofit kit, <b>for self-assembly</b>		4200 0280	
Transport wheels with drawbar	Plug in coupling for trailed press conversion	400 kg	6150 1020	
Rear headstock long for Simplex 420-56 - 710-56	with tined unit or FlatSpring	220 kg	6150 1010	
Hydraulic change over block	for hydraulic adjustment of the FlatSpring (saves 1x da control unit)		9700 7581	

### Additional information

Additional information	Note
Required hydraulic connections	1x da (Simplex) 1x da (FlatSpring)



Consider the traffic regulations! Restricted visibility must be observed.  
Equipment list for front devices see page 5.